

20
(Event)

GPS RACE DATA
Men's Lightweight Pair
28 MAY 2011

LM2-FA
Race 153

Dist. [m]	ITA1		GBR2		CZE		GER		SRB		ITA2	
	Speed [m/s]	Stroke	Speed [m/s]	Stroke	Speed [m/s]	Stroke	Speed [m/s]	Stroke	Speed [m/s]	Stroke	Speed [m/s]	Stroke
50	3.8	40.8	3.9	39.2	4.2	40.0	4.4	40.3	4.6	37.3	4.1	42.8
100	5.1	42.0	5.3	40.4	5.2	41.1	5.4	41.9	5.2	40.2	5.0	43.7
150	5.5	42.7	5.5	42.5	5.4	41.0	5.5	41.6	5.4	41.6	5.1	43.8
200	5.4	43.3	5.4	42.7	5.4	40.2	5.5	41.4	5.2	41.9	5.3	43.1
250	5.3	43.0	5.4	42.0	5.3	39.5	5.4	40.1	5.2	41.2	5.1	41.9
300	5.2	42.6	5.4	42.4	5.2	38.9	5.2	38.8	5.2	40.4	5.1	41.4
350	5.2	42.0	5.1	40.6	5.2	38.2	5.2	37.7	5.1	39.7	5.1	40.6
400	5.1	42.2	5.1	39.6	5.2	37.7	5.1	36.8	5.0	40.0	5.1	39.8
450	5.0	40.9	5.0	39.0	5.2	37.5	5.1	36.5	5.0	39.1	5.1	39.3
500	5.0	40.0	5.0	38.6	5.1	37.2	5.0	36.4	5.0	38.4	5.0	38.8
550	5.0	39.4	5.0	38.2	5.0	36.8	4.9	36.2	4.8	37.5	5.0	38.5
600	5.0	39.4	4.9	38.1	5.0	36.3	5.0	36.1	4.7	36.9	5.1	38.3
650	4.9	38.8	4.9	37.1	4.9	35.9	5.1	35.9	4.9	36.7	5.0	38.2
700	5.0	38.8	4.9	37.1	4.9	37.4	5.1	35.9	4.9	36.6	4.8	38.1
750	5.0	39.1	5.0	37.1	4.9	37.9	5.1	35.8	4.8	36.5	4.9	37.9
800	5.1	39.2	4.9	36.5	5.0	36.5	4.9	35.7	4.9	36.4	4.9	37.9
850	4.9	38.8	4.9	37.1	4.9	36.1	4.6	35.4	4.9	36.3	4.8	37.8
900	4.9	38.7	4.8	36.2	4.9	35.8	4.9	35.2	4.9	36.2	4.9	37.9
950	4.9	38.5	4.8	36.7	4.9	35.5	5.0	35.1	5.0	36.3	4.9	38.2
1000	4.9	38.4	4.9	36.5	4.9	35.5	5.0	35.2	5.1	36.3	5.1	38.3
1050	5.0	38.5	5.0	36.7	5.0	35.5	4.9	35.5	5.0	36.6	5.0	38.2
1100	4.9	38.5	4.9	36.8	4.8	35.5	4.9	35.6	5.0	36.6	4.9	38.0
1150	4.9	38.4	4.9	37.0	4.6	35.5	4.9	35.4	5.1	36.6	4.9	37.9
1200	4.9	38.2	4.8	36.3	4.8	35.4	4.7	35.2	5.0	36.6	4.8	37.9
1250	4.9	38.4	4.8	36.6	4.7	35.4	4.8	35.3	4.9	36.3	4.8	38.2
1300	4.9	38.3	4.8	37.1	4.9	35.4	5.0	35.6	4.8	36.4	4.9	38.3
1350	4.9	38.2	4.8	36.2	4.8	35.1	5.0	35.6	4.7	36.3	4.8	38.2
1400	4.9	38.3	4.8	37.2	4.9	35.0	4.9	35.9	4.9	36.4	4.9	38.1
1450	4.9	38.3	4.8	37.4	4.8	35.2	5.0	35.8	4.9	36.4	4.9	38.2
1500	4.8	38.3	4.9	37.2	4.9	35.3	4.9	35.7	4.9	36.6	5.0	38.2
1550	4.9	38.7	4.8	37.1	4.9	35.4	4.9	36.0	5.0	36.9	5.0	38.5
1600	5.0	39.2	4.9	36.8	4.9	35.5	4.9	36.2	5.0	37.2	4.9	38.7
1650	5.0	39.6	4.9	38.0	4.9	35.5	4.9	36.3	5.0	37.6	5.0	39.2
1700	5.0	40.0	4.8	37.7	4.9	35.7	4.9	36.3	5.1	38.1	4.9	39.0
1750	4.9	40.2	4.9	38.1	5.0	35.9	5.0	36.6	5.1	38.3	4.8	38.7
1800	5.0	40.6	5.0	38.7	5.0	36.3	4.9	37.1	5.1	38.7	4.8	38.5
1850	4.9	40.7	5.2	40.0	5.0	37.0	4.8	37.5	5.1	39.3	4.8	38.3
1900	5.0	41.4	5.2	40.7	5.1	38.0	4.9	38.0	5.1	39.8	4.8	38.6
1950	5.1	42.2	5.2	40.6	5.1	39.2	5.1	38.4	5.1	40.0	4.9	38.7
2000	5.0	42.3	5.3	41.2	5.0	40.3	5.0	39.0	5.0	40.0	4.7	38.4